

# AD-CMS-E

## Magnetic Contacts

### Magnetic surface contacts

#### AD-CMS01

Power contact for die-cast aluminum surface

- > Adapter for armored doors. Ends with terminals
- > Operating distance: 25 mm maximum

#### AD-CMS02

Surface contact, die-cast aluminum

- > Burglar-proof device
- > Minimum operating distance: 10 mm



### Flush-mounted contacts

#### AD-CME01

White ABS recessed contact

- > Diameter: 9 mm
- > Burglar-proof device
- > Operating distance: 10 mm maximum

#### AD-CME02

Recessed brass contact

- > Diameter: 8 mm
- > Burglar-proof device
- > Suitable for installations on aluminum or wooden closures
- > Operating distance: 10 mm maximum

#### AD-CME03

Recessed brass contact

- > Spacer diameters: 10 mm and 16 mm
- > Burglar-proof device
- > Suitable for installations on iron and armored doors
- > Operating distance: 20 mm maximum

#### AD-CME04

Recessed contact in ABS

- > Dimensions: Diameter 20 mm and Length 40 mm
- > Burglar-proof device
- > Operating distance: 20 mm maximum
- > Intensity: 0.5 A
- > Voltage: 24 V



AD-CME01



AD-CME02



AD-CME03



AD-CME04