

## RJ SECURE PATCH CORD

### AD-CCLC6AU-L-C Cat.6A UTP RJ Secure Patch Cord (Molding type optional)

Qualified The RJ Secure Patch Cord features a low-profile boot with an integrated lock that prevents normal disconnection.

The cord can only be removed with the use of the RJ Secure universal key\*. The unique plug and boot design incorporates a push-pull action which is based on Adtronics. This design provides excellent accessibility in high density environments.

The RJ Secure Patch Cord is offered in Category 6A F/UTP, UTP, and Category 6 UTP versions and is fully supported by Applicable Adtronics System Warranties.


### Specification:

Qualified Unscreened Cat.6A/Class EA (10G/500MHz) Connecting Hardware

Complied with IEC 60603-7-41  
 ISO/IEC 11801 2.2 Edition  
 CENELEC EN 50173-1:2011  
 ANSI/TIA-568-C.2

### Physicals:

Housing: PC, 94V-0  
 Loadbar: PC, 94V-0  
 Organizer: Metalized compound.  
 Contact Blade: 2-contact blade for stranded wire, phosphor bronze, gold over nickel plating  
 Boots: PP  
 Cable: Cat.6A U/UTP LSZH patch cable 4 pairs, 24AWG, stranded, OD Ø5.90mm.



References	Length	CoLor
AD-CCLC6AU-L-C	L=1, For a length of 1 m	C=G, For Grey
	L=2, For a length of 2 m	C=B, For blue
	L=3, For a length of 3 m	C=R, For Red
	L=5, For a length of 5 m	C=V, For Green
	L=7, For a length of 7 m	C=J, For yellow
	L=N, For Black	C=N, For Black