

## Fiber Optic ENCLOSURE

### Horizontal/In Line Fiber Optic Splice Closure

#### Application and Feature

- Can be used in straight-through and branch application for cables of bunchy fiber and ribbon fiber
- Suitable for aerial, duct, wall-mounted or buried applications
- Repeat open convenience
- IP68, IK10
- Slide-N-Lock fiber optic splice tray with its opening angle above 90°, Trays can be increased and reduced according to the application
- The plastic part is made of high-strength PC engineering plastic, which ensures a perfect performance in anti-aging and strength
- Perfect performance in sealing



<b>P/N</b>	AD-FOSC-D083	<b>Cable Diameter</b>	22(Max.)
<b>Dimension (L*W*H) mm</b>	323*202*86	<b>Max. Capacity (Bunchy fiber)</b>	96
<b>Cable Entry</b>	6	<b>No.of trays</b>	1-4

<b>P/N</b>	AD-FOSC-H003	<b>Cable Diameter</b>	14(Max.)
<b>Dimension</b>	280*200*90	<b>Max. Capacity</b>	96
<b>Cable Entry</b>	2	<b>No.of trays</b>	1-4

## Fiber Optic ENCLOSURE

### Horizontal/In Line Fiber Optic Splice Closure



<b>P/N</b>	AD-FOSC-H042	<b>Cable Diameter</b>	20(Max.)
<b>Dimension</b>	435*190*120	<b>Max. Capacity</b>	96
<b>Cable Entry</b>	4	<b>No.of trays</b>	1-4

<b>P/N</b>	AD-FOSC-H091	<b>Cable Diameter</b>	20(Max.)
<b>Dimension</b>	323*202*86	<b>Max. Capacity</b>	96
<b>Cable Entry</b>	6	<b>No.of trays</b>	1-4



<b>P/N</b>	AD-FOSC-H001	<b>Cable Diameter</b>	23(Max.)
<b>Dimension</b>	350*220*160	<b>Max. Capacity</b>	192
<b>Cable Entry</b>	6	<b>No.of trays</b>	1-8

<b>P/N</b>	AD-FOSC-H005	<b>Cable Diameter</b>	20(Max.)
<b>Dimension (L*W*H) mm</b>	390*210*120	<b>Max. Capacity (Bunchy fiber)</b>	96
<b>Cable Entry</b>	6	<b>No.of trays</b>	1-4