

AD-DVR0404/0804/1604HF-A-E

4/8/16CH 960H 1U Standalone DVR



Features

- ◆ Up to 4/8/16 cameras with 1080p realtime preview
- ◆ H.264 dual-stream video compression
- ◆ Full channel@960H(960× 576/960× 480) realtime recording
- ◆ HDMI/VGA/TV/Spot simultaneous video output
- ◆ All channel synchronous realtime playback, GRID interface & smart search
- ◆ 3D intelligent positioning with Dahua PTZ dome camera
- ◆ Support 2 SATA HDDs up to 8TB, 2 USB2.0
- ◆ Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

AD-DVR0404/0804/1604HF-A-E

Technical Specifications

Model	AD-DVR0404HF-A-E	AD-DVR0804HF-A-E	AD-DVR1604HF-A-E
System			
Main Processor	Dual-core embedded processor		
Operating System	Embedded LINUX		
Video			
Input	4 channel, BNC	8 channel, BNC	16 channel, BNC
Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s), Effio 960H camera		
Audio			
Input	4 channel, RCA	8 channel, RCA	4 channel, RCA
Output	1 channel, RCA		
Two-way Talk	1 channel Input, 1 channel Output(reuse the audio output channel), RCA		
Display			
Interface	1 HDMI, 1 VGA, 1 TV, 1 Spot, BNC(1.0Vp-p, 75Ω)		
Resolution	1920× 1080, 1280× 1024, 1280× 720, 1024× 768		
Display Split	1/4	1/4/8/9	1/4/8/9/16
Privacy Masking	4 rectangular zones (each camera)		
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording		
Recording			
Video/Audio Compression	H.264/G.711		
Resolution	960H(960× 576/960× 480)/D1/4CIF(704× 576/704× 480) / HD1(352× 576/352× 480) / 2CIF(704× 288/704× 240) / CIF(352× 288/352× 240) / QCIF(176× 144/176× 120)		
Record Rate	Main Stream:	960H/D1/HD1/2CIF/CIF(1~25/30fps)	
	Extra Stream	CIF/QCIF(1~25/30fps)	

AD-DVR0404/0804/1604HF-A-E

Technical Specifications

Bit Rate	48~3072Kb/s		
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop		
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec		
Video Detection & Alarm			
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips		
Video Detection	Motion Detection, MD Zones: 396(22× 18), Video Loss & Camera Blank		
Alarm Input	4 channel	8 channel	16 channel
Relay Output	3 channel		
Playback & Backup			
Sync Playback	1/4	1/4/9	1/4/9/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search		
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom		
Backup Mode	USB Device/Network/Internal SATA Device		
Network			
Ethernet	RJ-45 port (10/100M/1000M)		
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, Alarm Server		
Max. User Access	20 users		
Smart Phone	iPhone, iPad, Android, Windows Phone		
Storage			
Internal HDD	2 SATA ports, up to 8TB		

AD-DVR0404/0804/1604HF-A-E

Technical Specifications

Auxiliary Interface	
USB Interface	2 ports (1 Rear), USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	
Power Consumption	
Working	-10°C ~ +55°C / 10%~90%RH / 86~106kpa
Dimension(W×D× H)	1U, 375mm× 285mm× 50mm
Weight	2.35KG(without HDD)

System Connection

