

AD-NKB1000/AD-KBD1000/AD-KB1000

Network Keyboard & Control Keyboard & Dome keyboard



Features

Keyboard to Control

- ◆ ADTRONICS High Speed Dome (all models)
- ◆ ADTRONICS Standalone DVR (KBD1000 & NKB1000 only)
- ◆ ADTRONICS Network High Speed Dome (NKB1000 only)
- ◆ Network Video Server (NKB1000 only)

Connection

- ◆ NKB1000: RS485, RS422, USB, RS232 & Network
- ◆ KBD1000: RS485, RS422, USB & RS232
- ◆ KB1000 : RS485, RS422 & USB
- ◆ Three Dimensional Joystick Control of PTZ Functions
- ◆ Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- ◆ Auxiliary Functions
- ◆ On-Screen Menu & User Operation Procedure Tips
- ◆ Connect to SmartPSS via USB (NKB1000 only)

AD-NKB1000/AD-KBD1000/AD-KB1000

Features

Model	AD-NKB1000	AD-KBD1000	AD-KB1000
General			
Keyboard Keypanel	Electromechanical		
Joystick	3-axis, vector-solving, with twisting, return to-center head		
Keyboard Connector	RJ-45,RS232,RS485,RS422,USB,	RS232,RS485,RS422	RS485,RS422
Keyboard Communication	Direct Mode, Network Mode	Direct Mode	Direct Mode
Direct Mode	Interface: RS232/RS485 Dome Protocol: PELCO-D/PELCO-P/PELCO-D1/PELCO-P1.....		
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol	N/A	N/A
Display	LCD, 75.2mm x 33.85mm		
Environmental			
Power Supply	Power adapter, input 100V~240V 50Hz / 60Hz,output DC12V/100mA		
Power Consumption	5W		
Working Temperature	-10°C~+55°C		
Working Humidity	10%~90%		
Atmosphere Pressure	86kpa~106kpa		
Dimension	330mmx160(140)mmx37.5(21)mm (WxDxH) (height: 100mm including joystick)		
Weight	2.5KG		