

# AD-NVD0905DH-4I-4K

## Ultra-HD Network Video Decoder



### Features

- ◆ Designed for standalone operator viewers
- ◆ H.265/H.264/MJPEG/MPEG4/MPEG2 video decoding
- ◆ Ultra-high decoding ability, up to 12Mp
- ◆ 2ch HDMI and 2ch DVI-I input, 9ch HDMI output
- ◆ Support 1/4/9/16 display split
- ◆ Support audio, alarm, bi-directional talk, RS485
- ◆ Splicing screens control for zoom/merge/roam/overlay



# AD-NVD0905DH-4I-4K

## Features

System			
Processor	Intel x86 processor		
Operating System	LINUX		
Performance			
Video Format	MPEG2/MPEG4/H.264/H.265/MJPEG		
Audio Format	PCM/G711/AAC		
Decoding Capacity Separately	Port 1,2,3	Port 4,5,6	Port 7,8,9
	3CH@12MP/3CH@4K/;12CH@1080P/;27CH@720P/48CH@D1	3CH@12MP/3CH@4K/;12CH@1080P/;27CH@720P/48CH@D1	3CH@12MP/3CH@4K/;12CH@1080P/;27CH@720P/48CH@D1
Total Video Decoding	9CH@12MP/9CH@4K/36CH@1080P/81CH@720P/144CH@D1		
Decoding Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080P/720P/960H/D1/HD1/2CIF/CIF/QCIF		
Video Output	9ch HDMI		
Display Resolution	3840×2160/2560×1600/1920×1080/1280×1024/1280×720/1024×768, only 6 ports support 3840×2160, the remaining 3 ports support 2560×1600		
Audio Output	9ch HDMI		
Communication Interface	2 RJ45 network port (10M/100M/1000M); 3 RS232(1 DB9, 2 RJ45); 1 RS485		
Bi-directional Talk	1 Pair 3.5mm jack (2.0V Line in/50mV Mic in/10KΩ, 2.0V/16Ω out)		
Alarm Input	4ch		
Alarm Output	4ch relay out (30VDC 1A, 125VAC, 0.5A)		
Others			
Power Supply	AC100-240V, 50Hz-60Hz		
Power Consumption	≤70W		
Working Temperature	-10°C~+55°C		
Working Humidity	10% ~ 95%, 86Kpa ~ 106Kpa		
Unit Dimension	1.5U, 440mm×408mm×70mm(W*D*H)		
Weight	4.5kg-4.8kg		